

SAS Drybreak Range

Liquip Victoria's SAS range of dry-disconnect / dry-break couplings provide spill free product transfers for a wide range of media including Fuel, LPG, Ammonia, and other volatile chemicals.

Our couplers are designed to facilitate safe, affordable, and swift transfer of fluids and gases, while protecting the operator and the environment.



Integrity Manufacturing

We take pride in offering one of the highest-quality couplers available. To this end, all of our materials are sourced from, and manufactured in, the USA and Germany. Our products do not contain base metals or low-cost region sub-components.

QUALITY → SERVICE → SATISFACTION

There are many factors that distinguish our SAS couplers from other products on the market. Their ease of use, safety, and reliability make them an effective tool for preventing spills and leaks. In addition, they reduce product residue to one of the lowest levels in the industry. A broad range of energy, chemicals, and marine companies put our couplers to work wherever safety, efficiency, and the integrity of the product count most.

Technical Specifications

Coupler sizes: 1", 2", 2.5", 3", 4"
Pressure: 363 psi (Sst.), 232 psi (Alu.)
Connections: NPT, BSP / DIN, Flange
Body materials: Stainless steel, Aluminium
Seal types: Viton (others by request)



Key Advantages

- ✓ Minimized product residue
- ✓ Minimized purchase and lifetime costs
- ✓ Excellent transfer rates
- ✓ Safe handling of aggressive or valuable media
- ✓ Fire / pressure spike resistant design
- ✓ Easy maintenance process
- ✓ Integrated swivel functionality
- ✓ Short lead times and order turnarounds
- ✓ Intuitive One Motion Coupling™ technology
- ✓ Compatibility with NATO STANAG couplers

48 Vella Drive
Sunshine West,
VICTORIA, 3020.

Phone: (03) 9311 7822
Fax: 03 9311 8784
E-mail: sales@liquipvictoria.com.au

**SOLUTION FOCUSED
SERVICE DRIVEN**