

API-LI API Latching Indicator Gauge

The API-LI has been designed to provide users with a quick and efficient method to measure the latching capability of Liquip manufactured API couplers. i.e. API700, API800 and LYNX series.

The latching capability of the API coupler is measured instantly against pre-determined allowances and is visually represented allowing users to easily determine if the coupler is suitable for continued use or if it requires servicing.

When engaging the API-LI ensure you squeeze the stainless steel handle of the API coupler, as this will assist with the ease of engagement and increase the service life of the API-LI.



API-LI
Made in Stainless Steel 304

Visual Identification

- **RED** (only) visible:
Immediately remove coupler from service and conduct complete coupler maintenance.
- **GREEN** (only) visible:
Continue coupler use.
- **RED** and **GREEN** visible:
Continue coupler use.
Monitor and check again in 3-6 months.

Benefits

- Indicates latching integrity of API coupler.
- Quick and Easy to use.
- Visual indication of coupler latching capability.
- Can be used in situ.
- Stainless Steel 304 construction for durability.



API-LI connected to LYNX852



RED SHOWING
API coupler requires servicing



GREEN SHOWING
API coupler suitable for continued use

Note: The API-LI is intended to be used in conjunction with standard coupler maintenance. Liquip recommends users service couplers in line with Liquip's recommended coupler maintenance schedule.