## PIUSI PANTHER EX56 SERIES





Panther EX 56 230V 50HZ Feet

Pump suitable for Aviation Fuel

### **FEATURES**

- Panther Pump can be used with AVGAS 100/100LL (pump only) and JET A/A1 (pump only)
- ▶ High Flow Rate
- Heavy Duty
- Continuous Duty
- ► Thermal Protection
- UL Version Available
- Removable Pump Feet
- ► Up to 56L/Min
- Power: 240V AC
- Magnetic Switch



Made in Italy



Panther EX 56 230V 50HZ Drum

**Pump suitable for Aviation Fue** 

### HIGH PERFORMANCE | HIGH PRESSURE | CONTINUOUS DUTY

The new PANTHER EX56 AC pump series by PIUSI, designed for Heavy Duty applications, delivers superior performance and uncompromising reliability. Resulting from advanced research and development, this pump sets new standards with a flow rate of 56 l/min, the highest in its category. Capable of maintaining high performance even at high pressures, the PANTHER EX56 is ideal for various tank configurations and accessories, ensuring efficiency and versatility in every application.

#### KIT CONTENTS

#### Panther EX 56 - Drum Version

- Panther EX 56 Drum
- ► Nozzle Holder
- ► Drum Connector
- ► Instruction Manual

#### Panther EX 56 - Feet Version

- ➤ Panther EX 56-Feet
- ▶ Non-Mounted Feet
- ► Instruction Manual


#### **MATERIALS**

- ► Body Cast Iron
- Rotor Sintered Steel
- Vanes Technopolymer
- ► Seal Viton
- ➤ Shaft Steel


#### **DETAILS**

- ► On/Off Switch
- Vane Motor
- Bypass Valve

#### Panther EX 56 - Feet Version



Panther EX 56 - Drum Version



**Dimensions - Expressed in Millimetres** 










Bypass Valve

# PIUSI PANTHER EX56 SERIES





TECHNICAL DATA												
CODE	DESCRIPTION	METER ATEX	FLUID TYPE*	FLOWRATE		VOLTAGE			DUTY CYCLE		INLET	OUTLET
				L/MIN	GPM	AC VOLT /HZ	POWER WATT	AMP MAX		RPM		00.121
									CONTINUOUS		BSP	BSP
F00580000	Panther EX 56 230V 50HZ Feet	-	D, P, K, A**, J**	56	14.7	230V/50HZ	500	2.3	S1	2800	1"	1"
F00580010	Panther EX 56 230V 50HZ	-	D, P, K,	56	14.7	230V/50HZ	500	2.3	S1	2800	1"	1"

TECHNICAL DATA												
CODE	DESCRIPTION	METER ATEX	FLUID TYPE *	FLOWRATE		VOLTAGE			DUTY CYCLE			
				L/MIN	GРM	AC VOLT /HZ	POWER WATT	AMP MAX		RPM	INLET	OUTLET
									CONTINUOUS		BSP	BSP
F00580000	Panther EX 56 230V 50HZ Feet	K33	D, P, K	56	14.7	230V/50HZ	500	2.3	S1	2800	1"	1"
F00580010	Panther EX 56 230V 50HZ Drum	K33	D, P, K	56	14.7	230V/50HZ	500	2.3	S1	2800	1"	1"

<sup>\* (</sup>D) - DIESEL, (P) - PETROL, (K) - KEROSENE, (A) - AVGAS, (J) - JET A/A1

Drum

A\*\*, J\*\*

476 Boundary Rd Derrimut VICTORIA 3026

Phone: 03 9311 7822

E-mail: sales@liquipvictoria.com.au



<sup>\*\*</sup> Piusi Panther EX 56 can be used with AVGAS 100/100LL (pump only) and Jet A/A1 Fuels (pump only)