

“The Best Hose Suspension in the World”



MODEL
HB 100 ED
For
Hose I.D. 1” (2.5cm)



Material:	URETHANE	
Length:	16" / 40.6 cm	
Shipping Weight:	3 lbs / 1.4 kgs	
Shipping Dimensions:	21 x 8 x 4" / 53 x 21 x 10 cm	
Sling Model:	Metal "D-Ring" Sling	
Sling Type:	RS 16D	
*Sling height:	8" / 20 cm	
Sling Material:	UV Resistant Treated Polyester	
Rated Capacity:	1350 lbs/ 612 kgs @ 5:1 WLL	437 kgs/ 964 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C	

*Measured from top of the bun to the top of the sling

Notes: The most popular petroleum hose model Used throughout the world at refueling stations. Often used conjunction with retractors.

CE certified slings available at a rated capacity of 500 kgs @ 7:1

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



THE HOME OF **Fuelcraft**

“The Best Hose Suspension in the World”



MODEL
HB 125 ED

For

Hose I.D. 1¹/₄" (3.1 cm)



Material:	URETHANE	
Length:	17.5" / 44.45 cm	
Shipping Weight:	3.5 lbs / 1.6 kgs	
Shipping Dimensions:	21 x 8 x 4" / 53.4 x 21 x 10 cm	
Sling Model:	Metal "D-Ring" Sling	
Sling Type:	RS 16D	
*Sling height:	7" / 17.8 cm	
Sling Material:	UV Resistant Treated Polyester	
Rated Capacity:	1350 lbs/ 612 kgs @ 5:1 WLL	437 kgs/ 964 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C	

*Measured from top of the bun to the top of the sling

Notes: Used with petroleum hose, refueling stations with hyhose retractors, hydraulic hose bundles and theatrical cabling.

CE certified slings available at a rated capacity of 500 kgs @ 7:1

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



“The Best Hose Suspension in the World”



MODEL
HB 150 ED

For
Hose I.D. 1 1/2” (3.8cm)



Material:	URETHANE	
Length:	19.5" / 49.5 cm	
Shipping Weight:	4 lbs / 1.8 kgs	
Shipping Dimensions:	21 x 8 x 4" / 53 x 21 x 10 cm	
Sling Model:	Metal "D-Ring" Sling	
Sling Type:	RS 16D	
*Sling height:	6.5" / 16.5 cm	
Sling Material:	UV Resistant Treated Polyester	
Rated Capacity:	1350 lbs/ 612 kgs @ 5:1 WLL	437 kgs/ 964 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C	

*Measured from top of the bun to the top of the sling

Notes: Often used for bundled hoses/cables, like theatrical cable for lighting and sound.
CE certified slings available at a rated capacity of 500 kgs @ 7:1

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



“The Best Hose Suspension in the World”



MODEL
HB 200 ED
For
Hose I.D. 2” (5 cm)



Material:	URETHANE	
Length:	18" / 45.7 cm	
Shipping Weight:	4.5 lbs / 2 kgs	
Shipping Dimensions:	21 x 8 x 4" / 53 x 21 x 10 cm	
Sling Model:	Metal "D-Ring" Sling	
Sling Type:	RS 16D	
*Sling height:	7.25" / 18.4 cm	
Sling Material:	UV Resistant Treated Polyester	
Rated Capacity:	1350 lbs/ 612 kgs @ 5:1 WLL	437 kgs/ 964 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C	

*Measured from top of the bun to the top of the sling

Notes: Also available with Type 4 Hook-Eye sling (Model # RS 234H) for heavy duty jobs.

(WLL for RS 234H: 2000lb / 907kgs @ 5:1 or 648kgs / 1428lbs @ 7:1)

CE certified slings available at a rated capacity of 500 kgs @ 7:1

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



THE HOME OF **Fuelcraft**

“The Best Hose Suspension in the World”



MODEL
HB 300 D
For
Hose I.D. 3” (8 cm)



Material:	URETHANE	
Length:	12.75" / 32.4 cm	
Shipping Weight:	4.25 lbs / 1.93 kgs	
Shipping Dimensions:	13 x 6 x 5" / 32 x 15 x 12.5 cm	
Sling Model:	Metal "D-Ring" Sling	
Sling Type:	RS 234D	
*Sling height:	8" / 20 cm	
Sling Material:	UV Resistant Treated Polyester	
Rated Capacity:	2000 lbs/907 kgs @ 5:1 WLL	648 kgs/1428 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C	

*Measured from top of the bun to the top of the sling

Notes: Hosebun for 3" (7.6 cm) hose with "D-Ring" sling attachment for easier mounting.
CE certified slings available at a rated capacity of 1000 kgs @ 7:1

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



THE HOME OF **Fuelcraft**

“The Best Hose Suspension in the World”



MODEL
HB 300 H
For
Hose I.D. 3” (7.6 cm)



Material:	URETHANE
Length:	12.75" / 32.4 cm
Shipping Weight:	4.25 lbs / 1.9 kgs
Shipping Dimensions:	13 x 6 x 5" or 36 x 15 x 13 cm
Sling Type:	Type 4 Hook Eye
Sling Model:	RS 234H
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	14.75" / 37.5 cm
Sling Material:	UV Resistant Treated Polyester
Rated Capacity:	2000 lbs/907 kgs @ 5:1 WLL
	648 kgs/1429 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C

Notes: Hosebun for 3” (7.6cm) hose with type 4 hook eye sling for increased strength and work safety.
CE certified slings available at a rated capacity of 1000 kgs @ 7:1

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



“The Best Hose Suspension in the World”



MODEL
HB 400 D
For
Hose I.D. 4” (10 cm)



Material:	URETHANE	
Length:	11.5" / 21.22 cm	
Shipping Weight:	5 lbs / 2.27 kgs	
Shipping Dimensions:	13 x 8 x 7" / 32 x 20 x 18 cm	
Sling Model:	Metal "D-Ring" Sling	
Sling Type:	RS 234D	
*Sling height:	8" / 20 cm	
Sling Material:	UV Resistant Treated Polyester	
Rated Capacity:	2000 lbs/907 kgs @ 5:1 WLL	648 kgs/1428 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C	

*Measured from top of the bun to the top of the sling

Notes: Hosebun for 4" (10cm) hose with "D-Ring" sling attachment for easier mounting.
CE certified slings available at a rated capacity of 1000 kgs @ 7:1

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



THE HOME OF **Fuelcraft**

“The Best Hose Suspension in the World”



MODEL
HB 400 H
For
Hose I.D. 4” (10 cm)



Material:	URETHANE
Length:	11.5” / 28.75 cm
Shipping Weight:	5 lbs / 2.3 kgs
Shipping Dimensions:	13 x 8 x 7” or 32 x 20 x 18 cm
Sling Type:	Type 4 Hook Eye
Sling Model:	RS 234H
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	14.75” / 37.2 cm
Sling Material:	UV Resistant Treated Polyester
Rated Capacity:	2000 lbs/907 kgs @ 5:1 WLL
	648 kgs/1429 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C

Notes: Hosebun for 4” (10cm) hose with type 4 hook eye sling for increased strength and work safety.
CE certified slings available at a rated capacity of 1000 kgs @ 7:1

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



“The Best Hose Suspension in the World”



MODEL
HB 200 SRD
For
Hose I.D. 2” (5 cm)



Material:	URETHANE	
Length:	12" / 30.5 cm	
Shipping Weight:	2.5 lbs / 1.1 kgs	
Shipping Dimensions:	13 x 5 x 3.5" / 33 x 13 x 9 cm	
Sling Model:	Metal "D-Ring" Sling	
Sling Type:	RS 16D	
*Sling height:	7.25" / 18.4 cm	
Sling Material:	UV Resistant Treated Polyester	
Rated Capacity:	1350 lbs/ 612 kgs @ 5:1 WLL	437 kgs/ 964 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C	

*Measured from top of the bun to the top of the sling

Notes: Also available with Type 4 Hook-Eye sling (Model # RS 234H) for heavy duty jobs.

(WLL for RS 234H: 2000lb / 907kgs @ 5:1 or 648kgs / 1428lbs @ 7:1)

CE certified slings available at a rated capacity of 500 kgs @ 7:1

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



THE HOME OF **Fuelcraft**

“The Best Hose Suspension in the World”



MODEL
HB 600 H
For
Hose I.D. 6” (15 cm)



Material:	URETHANE
Length:	21.5" / 54.6 cm
Shipping Weight:	17 lbs / 7.7 kgs
Shipping Dimensions:	23 x 10 x 15" or 57 x 23 x 31 cm
Sling Type:	Type 4 Hook Eye
Sling Model:	RS 600H
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	22.5" / 57.15 cm
Sling Material:	UV Resistant Treated Polyester
Rated Capacity:	8000 lbs / 3629 kgs @ 5:1 WLL
	2590 kgs / 5700 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C

Notes: Use Heat Wrap to extend temperature capacity up to 1100°F / 593°C (Model# HW600).
For 5" ID hoses, please ask us about our hosebun liners to ensure a secure fit. (Model# HBL 600).
CE certified slings available at a rated capacity of 3000 kgs @ 7:1

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



THE HOME OF **Fuelcraft**

“The Best Hose Suspension in the World”



MODEL
HB 800 H
For
Hose I.D. 8” (20 cm)



Material:	URETHANE
Length:	30.5” / 77.5 cm
Shipping Weight:	37 lbs / 16.8 kgs
Shipping Dimensions:	32 x 12 x 15” or 81 x 31 x 38 cm
Sling Type:	Type 4 Hook Eye
Sling Model:	RS 800H
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	18” / 45.7 cm
Sling Material:	UV Resistant Treated Polyester
Rated Capacity:	12000 lbs / 5443 kgs @ 5:1 WLL
	3888 kgs / 8570 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C

Notes: Use Heat Wrap to extend temperature capacity up to 1100°F / 593°C (Model# HW800).
CE certified slings available at a rated capacity of 4000 kgs @ 7:1 WLL

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



THE HOME OF **Fuelcraft**

“The Best Hose Suspension in the World”



MODEL
HB 1000 H
For
Hose I.D. 10” (25 cm)



Material:	URETHANE
Length:	40.75" / 103.5 cm
Shipping Weight:	62 lbs / 28 kgs
Shipping Dimensions:	42 x 15 x 18" or 106 x 37.5 x 46 cm
Sling Type:	Type 4 Hook Eye
Sling Model:	RS 1000H
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	19.25" / 48.90 cm
Sling Material:	UV Resistant Treated Polyester
Rated Capacity:	15000 lbs / 6803 kgs @ 5:1 WLL
	4860 kgs / 10700 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C

Notes: Use Heat Wrap to extend temperature capacity up to 1100°F / 593°C (Model# HW 1000).
CE certified slings available at a rated capacity of 5000 kgs @ 7:1 WLL

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au



“The Best Hose Suspension in the World”



MODEL
HB 1200 H
For
Hose I.D. 12” (30 cm)



Material:	URETHANE
Length:	40.75” / 103.5 cm
Shipping Weight:	62 lbs / 28 kgs
Shipping Dimensions:	42 x 15 x 18” or 106 x 37.5 x 46 cm
Sling Type:	Type 4 Hook Eye
Sling Model:	RS 1000H
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	23.25” / 59.1 cm
Sling Material:	UV Resistant Treated Polyester
Rated Capacity:	15000 lbs / 6803 kgs @ 5:1 WLL
	4860 kgs / 10700 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C

Notes: Same mold as the HB 1000H but with a longer sling to accommodate a 12” (30cm) I.D. hose. Use Heat Wrap to extend temperature capacity up to 1100°F / 593°C (Model# HW 1200).
CE certified slings available at a rated capacity of 5000 kgs @ 7:1 WLL

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au

