

PIUSI SUZZAR ADBLUE TRANSFER PUMP

EN. The careful analysis of the market and the experience of handling aggressive fluid, such as AdBlue®, leads PIUSI to develop a new type of diaphragm pump equipped with electric motor without any dynamic seals. This solution provides a reliable industrial pump together with self priming capabilities.

PERFORMANCE

SUZZARBLUE AC PUMP

Technical features:

- Voltage 230/50 V
- Hose tail connection 3/4"
- Absence of dynamic seals
- ON/OFF switch
- 2 m cable with socket
- Duty cycle 20 min

SUZZARBLUE DC PUMP

Technical features:

- Voltage 12 / 24 V
- Hose tail connection 3/4"
- Absence of dynamic seals
- ON/OFF switch
- 2 m cable with clamps
- handle available
- Duty cycle 20 min

Flow-rate

up to
36 l/min
(up to 9,2 gpm)



REGISTERED
DESIGN

REGISTERED
DESIGN



PRODUCTS' RANGE WEIGHT AND PACKAGING

Code	Weight		Packaging		N. Boxes/ Europallet	
	kg	lbs	mm	pcs/ box	✈	🚚
F00203090	7	15,4	350x180x280	1	60	84
F00203100	7	15,4	350x180x280	1	60	84
F00204080	3,6	7,9	350x180x280	1	60	84
F00204090	3,6	7,9	350x180x280	1	60	84

PUMPS



Fluid Handling Innovation



THE HOME OF Fuelcraft



FEATURES

On/off switch



ON REQUEST

Kit handle



Code R16175010

PRODUCTS' RANGE TECHNICAL DATA

Code	Description	Fluids type	Flow-rate		Voltage				Cables mod.	Inlet - Outlet BSP	On/Off switch
			l/min	gpm	AC V./Hz DC Volt	rpm	Power Watt	Amp. max.			
F00203090	SuzzaraBlue AC pump 230/50	U	34	9	230/50	1450	400	1,95	YES	3/4"	YES
F00203100	SuzzaraBlue AC pump 120/60	U	34	9	120/60	1400	400	1,95	YES	3/4"	YES
F00204080	SuzzaraBlue DC pump 12V	U	36	9,2	12	2800	260	22	YES	3/4"	YES
F00204090	SuzzaraBlue DC pump 24V	U	36	9,2	24	2800	310	13	YES	3/4"	YES

476 Boundary Rd
Derrimut
VICTORIA 3026

Phone: 03 9311 7822
E-mail: sales@liquipvictoria.com.au

