
PIUSI EX 50 / 75 DC







PIUSI EX50 / EX75 DC

Compact and sturdy. Designed to transfer fluids from any type of tank.

The PIUSI EX50/EX75 DC is a transfer pump suitable for flammable fuels such as petrol, kerosene and diesel. It is fully compliant with ATEX/IECEx requirements for the usage in potentially explosive atmospheres. Designed to transfer flammable fluids from tanks of any type, this pump is available in DC version and is fitted with a bypass valve and can dispense up to 75 l/min, with reduced absorption to ensure a long life to the pump.

FEATURES

- ► Compact & Sturdy Design
- ► Flanged Components
- ► Anti-Noise Fliter
- ► Thermal Protection
- ➤ Suction unit with integrated filter (drum version)
- ▶ UL listed motor available

KIT CONTENTS

- ► EX 50/EX75 DC Pump
- ► Flanged Connection
- ► Instruction Manual


MATERIALS

- ► Body Cast Iron
- ► Rotor Sintered Steel
- ► Vanes PPS
- ► Seal Viton
- ► Shaft Steel


DETAILS

- ► On/Off Switch
- ► Flanged Connections
- ▶ 75 L/MIN flow rate
- ► DC 12V Voltage

Piusi EX 75 DC



141



252














Dimensions - Expressed in Millimetres

PIUSI EX 50 / 75 DC





Our pumps complies with the followig marking ATEX/IECEx									
				EX50	EX75	EX50	EX75		
II	2	G	EX	d	db	IIA	IIB	T4	Gb
Group	Category	Type of explosive atmosphere	Permanent Prefix	Protection Method		Gas Glass		Temperature Class	Equipment Protection Level

PACKAGING									
CODE	DESCRIPTION	WEIGHT	PACK	AGING	N.BOXES / EUROPALLET				
	DEGGIAN FIGH	KG	ММ	PCS/BOX	PLANE	SHIP			
F00371000	EX 50 12V DC ATEX	6.9	12	1	60	84			
F00380000	EX 70 12V DC ATEX	8	12	1	60	84			

TECHNICAL DATA										
CODE		FLUID TYPE*	FLOWRATE		VOLTAGE			DUTY CYCLE		OUTLET
	DESCRIPTION		L/MIN	GPM	AC VOLT /HZ	POWER WATT	AMP MAX	MINUTES	RPM	BSP
F00371000	EX 50 12V DC ATEX	D, P, K	50	13	12	250	21	30	2700	1"
F00380000	EX 70 12V DC ATEX	D, P, K	75	19.8	12	240	20	30	2700	1"

^{* (}D) - DIESEL, (P) - PETROL, (K) - KEROSENE

Upon request it is available with different voltages and 60 hz frequency. Compatible fluids: diesel, kerosene, petrol, petrol alcohol mixed max 15%, aspen 2/4

476 Boundary Rd Derrimut VICTORIA 3026

Phone: 03 9311 7822

E-mail: sales@liquipvictoria.com.au

