

PIUSI ST 200 AC DIESEL TRANSFER DISPENSING PUMP


EN. High flow rate portable dispenser unit. ST 200 dispenses diesel fuel at a rate of up to 200 l/min and controls the flow with great precision (+/- 1%) thanks to the oval-gear flow meter (on request).

The low weight of the unit and the possibility of fitting wheels make it easy to handle and suitable for operating on worksites on vehicles with large storage tanks. The unit features a sturdy steel frame.

PERFORMANCE

- Flow rate up to 200 l/min
- Continuous AC operation.
- Noise level below 75 dB

DIMENSIONS





PRODUCTS' RANGE WEIGHT AND PACKAGING

Code	Weight		Packaging		
	kg	lbs	mm	inch	pcs/box
F00315000	46	101	587x395x420	23,1x15,6x16,5	1
F16860000	-	-	-	-	-



Flow-rate
up to
200 l/min
(up to 52,7 gpm)



FEATURES



ON REQUEST



Flow rate:
20 -220 l/min
Accuracy: +/- 1%
Oval gear system
Code: FO0540000



Fow rate 280 l/min
with swivel
Code: F13249000



Code: F18798000
(delivery hose 10 mt
+ Camlock)
Code: F18799000
(delivery hose 20 mt
+ Camlock)

PRODUCTS RANGE TECHNICAL DATA

Code	Description	Fluids	Flow-rate		Voltage			Pump		Max pressure	Inlet
		type	l/min	gpm	AC V/Hz	Power Watt	Amp. max.	mod.	no.		
F00315000	ST 200 BASIC	D	200	52,7	230/50	2050	10	E 120	2	2,5	1" 1/2
F16860000	HANDY KIT (handle + wheels)	D	-	-	-	-	-	-	-	-	-

Upon request it is available with different voltages and 60 Hz frequency

48 Vella Drive
Sunshine West
VICTORIA 3020

Phone: (03) 9311 7822
Fax: (03) 9311 8784
E-mail: sales@liquipvictoria.com.au

